

## PURUS<sup>®</sup> 15W-40 NG ENGINE OIL

Manufactured with virgin base oils

### DESCRIPTION:

**PURUS<sup>®</sup> 15W-40 NG Engine Oil** is a high performance low ash engine oil formulated for lubrication of the crankcase and power compressor cylinders of spark-ignited two-and four cycle gas fueled engines.

**PURUS<sup>®</sup> 15W-40 NG Engine Oil** is formulated with highly refined premium base stocks, combined with high performance additive package containing ashless dispersants, oxidation and corrosion inhibitors, antifoam and anti-wear agents. It is suitable for use in mobile applications such as trucks and buses equipped with engines fueled by compressed natural gas and liquid natural gas. This oil meets the performance requirements of mobile CNG and LNG engine manufacturers such as Cummins and Detroit Diesel. It is suitable for use for engines equipped with turbochargers and/or catalytic converters. This product is formulated for applications recommending Cummins CES 20074 Specification, and Detroit Diesel Specification 93K216.

### TYPICAL PROPERTIES:

	SAE Viscosity	15W-40
	@40 °C, cSt	120
	@100 °C, cSt	15.6
	Viscosity Index	137
	API Gravity	30.5
	Sp. Gravity	0.8735
	Flash, COC, °F	450
	Pour Pt., °F	-31
	Sulfated Ash	0.54
	Zinc, ppm	800
	Phosphorus, ppm	730
	TBN, ASTM D2896	5.6