

## PURUS® HEAVY DUTY FLEET ENGINE OILS

Manufactured with virgin base oils

**DESCRIPTION:** **PURUS® Premium Heavy Duty Fleet Engine Oils** combine high quality base oils with high performance additives to provide superb performance in the areas of detergency and dispersancy and protection against wear, rust, corrosion and high temperature thickening.

Premium Heavy Duty Fleet Engine Oils are premium HD engine oils meeting API CF (10WT) and obsolete CF, CF-2 (30WT, 40WT) for use in both turbo-charged and naturally aspirated diesel engines. They meet the requirements of 2-cycle diesel engines made before 2007. The SAE 10WT and 30WT are suitable for use in applications calling for Caterpillar TO-2 specification.

**APPLICATIONS:** **PURUS® Premium Heavy Duty Fleet Engine Oils** are premium HD engine oils meeting API CF (10WT) and CF, CF-2 (30WT, 40WT) for use in both turbo-charged and naturally aspirated diesel engines. They meet the requirements of 2-cycle diesel engines made before 2007. The SAE 10WT and 30WT are suitable for use in applications calling for Caterpillar TO-2 specification.

- PERFORMANCE BENEFITS:**
- Resists breakdown under high temperatures
  - Maintains oil pressure under heavy load conditions
  - Minimized rust and corrosion

**TYPICAL PROPERTIES:**

<b>SAE Viscosity</b>	<b>10</b>	<b>30</b>	<b>40</b>
Flash, COC °F	430	460	470
Pour Pt ° C	-30	-20	-15
Viscosity, cSt @100 °C	6.5	11.6	15.2
Viscosity Index	95	95	95
Sulfated Ash, Wt. %	0.9	0.9	0.9



Revised: 05/13

PHDHDFT