

PURUS[®] WAY OILS

Manufactured with virgin base oils

DESCRIPTION: **PURUS[®] Way Oils** are designed for lubricating the ways of all types of machine tools and other applications where a tacky, high film strength, extreme pressure properties are required. **PURUS[®] Way Oils** are blended from highly refined base oils and have been fortified with select additives and adhesive agents to impart excellent lubricity and extreme pressure properties. A high lubricity character helps to reduce friction and drag that can cause “stick-slip” problems and machine tool carriage chatter. The extreme pressure additives and the high film strength of the **PURUS[®] Way Oils** effectively control wear and galling of system components. This is achieved by exhibiting high film strength while a special tackifier prevents the fluid from draining away from the lubricated surface and minimizes squeeze out on heavily loaded ways.

**PERFORMANCE
BENEFITS:**

- Strong adhesive properties
- Good extreme pressure and anti-wear protection
- Excellent anti-stick-slip characteristics
- High film strength
- Smooth machine tool operations
- Good corrosion protection

TYPICAL PROPERTIES:	ISO VG	32	68	220
	Viscosity			
	@ 40°C cSt	32	68	220
	Viscosity Index	107	97	94
	Pour Point	-20° C	-20° C	-10° C



Updated: 05/13

PINWAY