

PURUS[®] SYNTHETIC BLEND SAE 10W-30 FA-4 HEAVY DUTY ENGINE OIL

Manufactured with highly refined base oils and industry leading additive chemistry

DESCRIPTION: **PURUS[®] Synthetic Blend SAE 10W-30 FA-4 Heavy Duty Diesel Engine Oil** is specially formulated for use in select high-speed four-stroke cycle diesel engines designed to meet 2017 model year on-highway greenhouse gas (GHG) emission standards. This oil is formulated to use in on-highway applications with diesel fuel sulfur content up to 15 ppm (0.0015% by weight). It is blended to a high temperature high shear (HTHS) viscosity range of 2.9 cP-3.2 cP to assist in reducing GHG emissions. It is especially effective at sustaining emission control system durability where particle filters and other advanced aftertreatment systems are used. **PURUS[®] Synthetic Blend SAE 10W-30 FA-4 Heavy Duty Diesel Engine Oil** is designed to provide enhanced protection against oil oxidation, viscosity loss due to shear, and oil aeration as well as protection against catalyst poisoning, particulate filter blocking, engine wear, piston deposits, degradation of low- and high-temperature properties, and soot-related viscosity increase.

APPLICATIONS: **PURUS[®] SAE 10W-30 API FA-4 Synthetic Blend Diesel Engine Oil** meets or exceeds API Service Classification FA-4, Cummins[®] CES 20087 and Detroit[™] DFS 93K223. NOTE: API FA-4 oils are **NOT** interchangeable or backward compatible with API CK-4, CJ-4, CI-4 Plus, CI-4 and CH-4 oils. Refer to individual engine manufacturer recommendations regarding compatibility with API FA-4 oils.

- PERFORMANCE BENEFITS:**
- Protects emission control systems
 - Outstanding oxidation stability
 - Excellent low temperature properties helps speed cold starts

TYPICAL PROPERTIES*:	Viscosity		
		@ 40° C, cST	D445 66.5
		@ 100°C, cST	D445 10.1
	Viscosity Index		D2270 137
	Pour Point °C (°F)		D97 -33 (-27)
	Flash Point °C (°F)		D92 238 (460)
	Sulfated Ash, wt.%		D874 1
	Cold Crank Simulator, cP		D5293 6040/-25°C
	Mini-Rotary Viscometer TP1, cP		D4684 18000/-30°C
	High Temperature High Shear, HTHS @150°C, cP		D4683 3.1
TBN		D2896 10	

*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.



PHD1030FA4

Updated: 04/17