

PURUS® HEAVY DUTY FULL SYNTHETIC AUTOMATIC TRANSMISSION FLUID

DESCRIPTION: **PURUS® Heavy Duty Full Synthetic Automatic Transmission Fluid** is a new generation automatic transmission fluid meeting the requirements of the JASO M315-2013 1-A specification for service fill fluid in the following automobile and truck transmissions, power shift transmissions and other types of service: FCA (Chrysler ASRC); Ford (FNR5); Hyundai (ATF RED-1K, SP-III); Isuzu (Genuine ATF); Jaguar (K17); Kia (SP-III); Land Rover (AW-1, N402); Mazda (ATF M-V); Mitsubishi (ATF-J2, SP-III); Nissan (Fluid A, Matic D, Matic J, Matic K); Saab (ATF AP); Subaru (ATF HP, P/N K0140Y0700); Suzuki (Matic D, Matic J), Toyota (JWS 3309, Type T, T-III, T-IV); VW (G 052 025). Also recommended for service fill in the following automobile and truck transmissions, power-shift transmissions and other types of service, based on extensive testing: BMW (83 22 2 163 514, ETL-7045, ETL-7045 E, ETL-8072 B, LA2634, LT 71141); FCA/Chrysler Type +3, +4; Ford (P/N Xt-2QDX, P/N XT-5-QM); GM (6032 M {IID}, 6137M {IIE}, 6417M {IIIG}, 10055 {IIIH}); Honda (ATF-Z1); Mercedes (3403 M115, 236.1, 236.6, 236.7, 236.8, 236.9, 236.10, 236.11); Saab (ATF-Z1); VW (GUS 00 162). It is suitable for use in Voith Transmissions as well as Allison Transmissions for extended drain.

PURUS® Heavy Duty Full Synthetic Automatic Transmission Fluid is suitable for use in applications where the OEM specifies a fluid proving performance capability comparable to the Allison TES 295® specification. This product is not certified by Allison Transmission under the TES 295® specification.

NOTE: PURUS® Heavy Duty Full Synthetic Automatic Transmission Fluid is not for use in transmissions requiring Ford Type F, DEXRON®-VI, MERCON® SP, MERCON® LV or in Continuously Variable Transmission (CVT) or Double Clutch Transmission (DCT) applications. Always consult your owner's manual where specific automatic transmission fluids are recommended.

- Outstanding resistance to oxidative and thermal breakdown
- Exceptional low temperature fluidity
- Excellent anti-wear properties
- Excellent gear shift quality throughout service life

TYPICAL PROPERTIES*:	Gravity, API	38.1
	Density, lbs/gals	6.93
	Flash, COC, °F	375
	Viscosity	
	@ 40 Deg. °C, cSt	35.8
	@ 100 Deg. °F, cSt	7.2
	Viscosity Index	170
	Brookfield Viscosity	
cP @ -40°C	8,060	
Color	Red	



* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

Revised: 08/17