

PURUS® ROCK DRILL OILS

Manufactured with high refined base oils

DESCRIPTION: PURUS® Rock Drill Oils are blended from highly refined base oils and special additives which produce an excellent lubricant for air powered equipment. The naturally high viscosity index provides optimum lubrication for both low start-up temperatures and high operating temperatures. Extreme pressure additives prevent wear and withstand the high loads commonly encountered in rock drills, jack hammers, pavement breakers, stoppers, drifters and down hole drills. PURUS® Rock Drill Oils are designed for use in both construction and mining equipment, and other pneumatic equipment applications.

PURUS® Rock Drill Oils atomize readily to insure lubricant distribution and rapid “wetting” of all parts of the equipment. By emulsifying with water, they also form a wash off resistant lubricant coating to help prevent rusting of critical components.

PURUS® Rock Drill Oils contain tackifying agents that provides for lubricant adherence to cylinder walls and other lubricated parts. They are fortified with extreme pressure additives that protect rock drills against wear caused by shock loads.

**PERFORMANCE
BENEFITS:**

- High film strength and extreme pressure properties to withstand shock loads and prevent wear
- Exceptional protection against rust and corrosion
- Excellent anti-foam capabilities
- Excellent adhesion
- Emulsifies with water readily

**TYPICAL
PROPERTIES*:**

	68	100	150	220	460
ISO VG	68	100	150	220	460
Gravity, API	29.5	28.1	27.2	27.4	26.5
Viscosity					
@ 40 °C, cSt	68	100	150	220	470
@100 °C, cSt	8.7	11.4	15	19.4	33.4
Viscosity Index	100	100	100	100	105
Pour Point °F	-20	-5	0	5	10



*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD

Distributor if you require any further information

PINRDO

Updated: 08/17