

PURUS® FULL SYNTHETIC AW PREMIUM HYDRAULIC OILS

Manufactured with highly refined base oils

DESCRIPTION: PURUS® Full Synthetic AW Premium Hydraulic Oils are premium quality anti-wear hydraulic oils, which are formulation using advanced zinc based anti-wear additive technology, combined with full synthetic base oils.

APPLICATION: PURUS® Full Synthetic AW Premium Hydraulic Oils are recommended for applications calling for: Fives Cincinnati (formerly MAG Cincinnati, Cincinnati Machin, Cincinnati Milacron), Parker Hannifin (Denison) HF-0, HF-1, HF-2, Eaton(formerly Vickers) M-2950-S and I-286-S, Passes Vickers 35VQ25 and V104C (ASTM D2882) vane pump tests, passes Denison P-46 piston pump and T-6C vane pump tests, U.S. Steel 127 and 136, and DIN 51524 Part II.

- PERFORMANCE BENEFITS:**
- High Viscosity Index (VI) for increased temperature range
 - Excellent wear protection
 - Outstanding oxidation and thermal stability for long life
 - Rapid release of entrained air
 - Excellent rust and corrosion protection and easy filterability

TYPICAL PROPERTIES*:	22	32	46	68	
ISO Viscosity Grade	22	32	46	68	
SAE Viscosity Grade	5W	10W	20W	20W	
Specific Gravity	0.837	0.843	0.846	0.845	
Flash Point °F (°C)	405 (208)	405 (208)	410 (210)	410 (210)	
Pour Point °F.	-40	-40	-40	-30	
Color	1.5	1.5	1.5	1.5	
Viscosity					
	@ 40 °C, cSt	20.3	32.3	47.1	68.8
	@100 °C, cSt	4.3	6	8.4	10.7
Viscosity Index	124	132	154	145	
Gravity, °API	37.7	36.4	35.7	36	
Rust Test, ASTM D665	Pass	Pass	Pass	Pass	
Oxidation, ASTM D943	>6000	>6000	>6000	>6000	
Total Acid Number, ASTM D664	0.6	0.6	0.6	0.6	
Dielectric Strength**, ASTM D877, Pail	35kV	35kV	35kV	35kV	

** Dielectric strength and conductivity value applies at "point of manufacture" of packaged product from AIOD manufacturing facility and will change if oil becomes contaminated with dirt or even a small amount of water

*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.



Revised: 12/17