

## PURUS® SAE 40 MANUAL HEAVY DUTY SYNTHETIC TRANSMISSION FLUID

**EATON APPROVED**

**Manufactured with highly refined base oils**

**DESCRIPTION:**

PURUS® SAE 40 Manual Heavy Duty Synthetic Transmission Fluid is a specially formulated synthetic lubricant designed for fuel efficiency, extended drain intervals and severe service in heavy duty commercial vehicle transmissions which require a non-EP transmission lubricant. It is formulated to protect high torque transmissions coupled with increased horsepower engines. It is approved for use in Eaton transmissions such as Ultrashift Plus, Fuller Advantage, FR and RT Series transmissions. It is not suitable for hypoid gear applications in differentials and final drives, either for topping-off or refills, where API Service GL-5 or SAE J2360 lubricants are specified. Eaton PS-386 (supersedes PS164 Rev 7)

**PERFORMANCE BENEFITS:**

- Mack TO-A Plus
- Navistar MPAPS-B-6816 Type II
- API MT-1
- Up to 1.5% fuel economy improvement
- Provides high performance and extended drain capabilities
- Excellent shear stability to ensure smooth transmission operation
- Excellent thermal and oxidation stability



**TYPICAL PROPERTIES\*:**

SAE Viscosity Grade		40
Viscosity	ASTM D 445	
@ 40°C, cSt		95.1
@100°C, cSt		14.8
Viscosity Index	ASTM D 2270	163
Pour Point, °F (°C)	ASTM D 97	-44 (-42)
Flash Point, °F (°C)	ASTM D 92	460 (238)
Gravity, API	ASTM D 287	34.9

**⚠ WARNING:** This product can expose you to chemicals including ANILINE, which is known to the State of California to cause cancer. For more information, go to: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

Revised:09/2019

PHDSAE40