

PURUS® ZINC FREE AW HYDRAULIC OILS

Manufactured with highly refined base oils

DESCRIPTION: PURUS® Zinc Free AW Hydraulic Oils are premium quality anti-wear hydraulic oils which are formulated using non-zinc containing additive technology. These products provide the product performance of premium anti-wear hydraulic oil, without the heavy metals which reduces concerns of many regulatory agencies. PURUS® Zinc Free AW Hydraulic Oils are non-toxic to fish and aquatic species as determined by OECD Test Method 203 and is classified as inherently biodegradable by OECD Test Method 301B.

APPLICATIONS: PURUS® Zinc Free AW Hydraulic Oils are recommended for use in all applications calling for anti-wear hydraulic oil and meet or exceed the current and former specifications: Fives Cincinnati P-68, P-69, P-70 (obsolete), Parker (formerly Denison) HF-0, HF-1, and HF-2, Eaton E-FDGN-TB002-E, Bosch Rexroth RDE 90220 (obsolete) and 90235, DIN 51524-II (HM), ASTM D6158 (HM), ISO 11158 (HM), AIST 126, 127, SAE MS 1004 (HM), GM LS2, SEB 181222, and JCMAS P041 HK Hydraulic specification. Inherently Biodegradable and non-toxic to aquatic organisms.

Suitable for use in applications which cite former or obsolete specifications such as Fives Cincinnati P-68, P-69, P-70 and Bosch Rexroth RDE 90220.

- Excellent wear protection and rapid release of any entrained air
- Oxidation and thermal stability for long life
- Excellent rust and corrosion protection and easy filterability

TYPICAL PROPERTIES*:

	32	46	68
ISO Viscosity Grade	32	46	68
SAE Viscosity Grade	10W	20W	20W
Specific Gravity	0.858	0.862	0.865
Flash Point °F (°C)	421 (216)	444 (229)	466 (241)
Pour Point °C	-39	-39	-36
Appearance	Light Pale	Light Pale	Light Pale
Viscosity			
@ 40 °C, cSt	32.53	46.85	69.04
@100 °C, cSt	6.39	8.39	10.84
@ 100 °F, SUS	165	227	352
@ 210 °F, SUS	44	48	56
Viscosity Index	153	156	150
Gravity, °API	31.5	30	28.5
Oxidation, ASTM D943, hours	>10000	>10000	>10000
Aquatic Toxicity, OECD 203	Nontoxic	Nontoxic	Nontoxic
Biodegradability in 28 days, OECD 301-B, %	72	72	72

*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

Revised: 05/2019
PHDZFAWHYD