

PURUS[®]

CUT THE COST, NOT THE QUALITY.

"YOU CAN TAKE IT TO THE LAB."

PURUS[®] ALLETOR[®] HEAVY DUTY HI-TEMP GREASE - 5% MOLY



DESCRIPTION

PURUS ALLETOR HEAVY DUTY HI-TEMP GREASE WITH 5% MOLY is a premium quality lithium complex grease treated with 5% molybdenum disulfide for additional protection against wear. It is available in NLGI #1 and NLGI #2 grades. It has excellent water spray-off and washout resistance, gives excellent performance in the areas of oxidation stability and corrosion protection and resists leakage, dripping or undesirable throw-off from the lubricated surface.

PURUS ALLETOR HEAVY DUTY HI-TEMP GREASE WITH 5% MOLY are purpose built to meet these industry drivers and challenges:

- Increased Equipment Loads & Extreme Pressure Conditions
- Harsh Wet & Contaminated Operating Environments
- Demand for Longer Lubrication Life & Reduced Maintenance

PERFORMANCE BENEFITS

INDUSTRY DRIVERS	PURUS SUPPORTING TECHNOLOGY	PURUS BENEFITS PERFORMANCE ADVANTAGES
Increased Equipment Loads & Extreme Pressure Conditions	<ul style="list-style-type: none">• 5% Molybdenum Disulfide (Moly) additive• Extreme Pressure (EP) lithium complex grease• High Four-Ball EP Weld Point (500 kgf)	<ul style="list-style-type: none">• Provides an extra layer of protection under severe loads and shock conditions• Reduces metal-to-metal contact and wear in high-stress applications• Extends equipment life in mining, construction, trucking, and off-road equipment• Excellent for wheel bearings, universal joints, and heavy-duty industrial applications
Harsh Wet & Contaminated Operating Environments	<ul style="list-style-type: none">• Outstanding water spray-off and washout resistance• Rust and corrosion inhibitors• Tacky lithium complex formulation	<ul style="list-style-type: none">• Protects components in wet, muddy, and contaminated environments• Minimizes lubricant washout and maintains film strength• Prevents rust and corrosion on critical components• Improves reliability and uptime for off-highway and industrial equipment
Demand for Longer Lubrication Life & Reduced Maintenance	<ul style="list-style-type: none">• Oxidation-stable lithium complex thickener• Resistance to leakage, dripping, and throw-off• Stay-in-place tacky grease structure	<ul style="list-style-type: none">• Reduces grease loss during operation• Extends relubrication intervals and lowers maintenance costs• Keeps protection in place during high-speed or vibrating operations• Excellent for fifth wheels and severe-duty on/off-road applications

PURUS[®]

CUT THE COST, NOT THE QUALITY.

"YOU CAN TAKE IT TO THE LAB."

TYPICAL PROPERTIES*

NLGI Number	NLGI #1	NLGI #2
NLGI Certified, ASTM D-4950	GC-LB	GC-LB
Thickener	Lithium Complex	Lithium Complex
Lubricating Solids Type	MoS2	MoS2
Lubricating Solids, weight %	5%	5%
Texture	Smooth, Tacky	Smooth, Tacky
Color, Observed	GRAY/BLACK	GRAY/BLACK
Worked 60 Penetration, D-217	310-340	265-295
Dropping Point, D-566, °F	>500	>500
Base Oil Viscosity @ 40°C-100°C, cSt	471-31	471-31
Water Washout, D-1264, % loss @ 175°F	5	2.5
Copper Corrosion, ASTM D-4048, rating	1B	1B
Rust Prevention, ASTM D1743, rating	Pass	Pass
Four-Ball Wear, ASTM D-2266, mm	0.4	0.4
Four-Ball EP Weld Point, D-2596, kgf	500	500
Timken OK Load, ASTM D-2509, lb.	70+	80+
Approximate Temperature Range, °F (°C)	-5 to 350 (-20 to 176)	-5 to 350 (-20 to 176)



*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

PRODUCT	Disposable Tote	400 LB Drum	120 LB Keg	35 LB Pail	50-10/14oz Tube
NLGI #1	PIN87326	PIN17326	PIN37326	PIN27326	PIN00431
NLGI #2	PIN87325	PIN17325	PIN37325	PIN27325	PIN00429