

PURUS[®]

CUT THE COST, NOT THE QUALITY.

"YOU CAN TAKE IT TO THE LAB."

PURUS[®] AKELA[™] NATURAL GAS ENGINE OILS-PREMIUM ASHLESS



DESCRIPTION

PURUS[®] AKELA[™] Premium Ashless Gas Engine Oils are formulated to provide excellent control of deposits, wear, oil oxidation and oil nitration in naturally aspirated and turbocharged 2 cycle natural gas engines and light duty 4 cycle engines. They are available in SAE 30 and SAE 40 viscosity grades and a SAE 15W40 multi-grade.

PURUS[®] AKELA[™] Premium Ashless Gas Engine Oils are specifically formulated to minimize deposits on valves, piston crowns and in the combustion chamber. These oils provide excellent copper-lead bearing corrosion protection, minimize port deposits thus extending port cleaning intervals and reducing maintenance costs. PURUS[®] AKELA[™] Premium Ashless Gas Engine Oils provide exceptional engine cleanliness under both high and low temperature operating conditions. These oils minimize viscosity increase and do not contribute to pre-ignition. PURUS[®] AKELA[™] Premium Ashless Gas Engine Oils meet the requirements for Dresser-Rand Categories I and II, as well as the requirements for other leading gas engine manufacturers requiring ashless type engine oils.

TYPICAL PROPERTIES*

	SAE 30	SAE 40	SAE 15W-40
API Gravity @ 60 F	31.4	30.1	29.6
Kinematic Viscosity @ 40C	98	122	113
Kinematic Viscosity @ 100C	11	13.4	14.4
Viscosity Index	103	103	130
Phosphorous	<800	<800	<800
TBN	.07	.07	.07
Sulfated Ash	<.1	<.1	<.1
Color	2	2	2
Pour C (F)	-30(-22)	-30(-22)	-30(-22)
Flash C (F)	260(500)	260(500)	260(500)

*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification.

Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

PRODUCT	55 Gal. Drum	Tote	Bulk
SAE 30	PG017211	PG057211	17211
SAE 40	PG017212	PG057212	17212
SAE 15W-40	PG017213	PG057213	17213