

PURUS[®]

CUT THE COST, NOT THE QUALITY.

"YOU CAN TAKE IT TO THE LAB."

PURUS[®] AKELA[™] MEDIUM ASH GAS ENGINE OIL SAE 40 10 TBN



DESCRIPTION

PURUS[®] AKELA[™] Medium Ash Gas Engine Oil SAE 40 10 TBN is a premium engine lubricant formulated with field-proven additive system. It provides excellent deposit, sludge and wear protections during high stress service. The base stocks and additive package combine to provide excellent dispersancy and detergency to reduce deposit formation due to nitration and to help prevent carbon and ash deposits during service. The outstanding base number retention combats oil degradation and provides protection in highly acidic environments.

PURUS[®] AKELA[™] Medium Ash Gas Engine Oil SAE 40 10 TBN is formulated for use in medium to high speed gas engines fueled with biogas, landfill gas, sewage digester gas, synthetic gas, and natural gas. PURUS[®] AKELA[™] Medium Ash Gas Engine Oil SAE 40 10 TBN oil meets the performance requirements of major engine manufacturers such as Deutz-MWM, Guascor, Jenbacher, Wartsila, Waukesha and other turbocharged and naturally aspirated medium to high speed engines.

TYPICAL PROPERTIES*

	SAE 40
Pour Point Deg. F.	-17
Flash Point, COC, °F	500
Viscosity @40 °C, cSt	125
Viscosity @100 °C, cSt	13.3
Viscosity Index	100
Gravity, API	29
Sulfated Ash	0.97
TBN, ASTM D 2896	10
Zinc, ppm	270
Phosphorus, ppm	250

*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification.
Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

PRODUCT	55 Gal. Drum	Tote	Bulk
SAE40	PG017241	PG057241	17241