

# PURUS<sup>®</sup>

## CUT THE COST, NOT THE QUALITY.

“YOU CAN TAKE IT TO THE LAB.”

## PURUS<sup>®</sup> HEAVY DUTY FLEET ENGINE OILS



### DESCRIPTION

PURUS<sup>®</sup> Heavy Duty Fleet Engine Oils combine high quality base oils with high performance additives to provide superb performance in the areas of detergency and dispersancy and protection against wear, rust, corrosion and high temperature thickening. These premium HD engine oils meet API CF (10WT) and obsolete CF, CF-2 (30WT, 40WT) for use in both turbo-charged and naturally aspired diesel engines. They meet the requirements of 2-cycle diesel engines made before 2007. The SAE 10WT and 30WT are suitable for use in applications calling for Caterpillar TO-2 specification.

PURUS<sup>®</sup> Heavy Duty Fleet Engine Oils are premium HD engine oils meeting API CF (10WT) and CF, CF-2 (30WT, 40WT) for use in both turbo-charged and naturally aspired diesel engines. They meet the requirements of 2-cycle diesel engines made before 2007. The SAE 10WT and 30WT are suitable for use in applications calling for Caterpillar TO-2 specification. CAUTION: THIS OIL IS RATED API PERFORMANCE CATEGORY CF. IT IS NOT SUITABLE FOR USE IN MOST DIESEL POWERED AUTOMOTIVE ENGINES BUILT AFTER 2009. LATER “C” CATEGORY OILS ARE USUALLY SUITABLE OR PREFERRED FOR DIESEL AUTOMOTIVE ENGINE FOR WHICH “CF” OILS WERE SPECIFIED. OLDER EQUIPMENT AND/OR TWO-STROKE DIESEL ENGINES, ESPECIALLY THOSE CALLING FOR MONOGRADE PRODUCTS, MAY HOWEVER REQUIRE “CF” CATEGORY OIL. CONSULT WITH YOUR ENGINE MANUFACTURER TO ENSURE YOUR EQUIPMENT IS STILL BEST SERVED BY CF CATEGORY PRODUCTS.

### TYPICAL PROPERTIES\*

WT	10	30	40
Flash, COC °F	430	460	470
Pour Pt ° C	-30	-20	-15
Viscosity @100° C, cSt	6.5	11.6	15.2
Viscosity Index	95	95	95
Sulfated Ash, Wt. %	0.9	0.9	0.9

\*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification.

Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

PRODUCT	5 Gal Pail	55 Gal Drum	Tote	Bulk
10WT	PHD27236	PHD17236	PHD57236	17236
30WT	PHD27234	PHD17234	PHD57234	17234
40WT	PHD27235	PHD17235	PHD57235	17235