

PURUS[®]

CUT THE COST, NOT THE QUALITY.

“YOU CAN TAKE IT TO THE LAB.”

PURUS[®] PREMIUM GL-5 LIMITED SLIP GEAR OILS



DESCRIPTION

PURUS[®] Premium GL-5 Gear Oils are multi-purpose sulfur/phosphorous gear lubricants designed for API Service Classification “GL-5” and “MT-1”. These premium gear oils are compounded with highly refined base stocks and additives to ensure extreme pressure characteristics, anti-wear, corrosion inhibition, rust prevention, low pour point, and anti-foaming performance. They are fully formulated for limited slip differentials.

PURUS[®] Premium GL-5 Gear Oils meet the requirements of U.S. Military Specification SAE J2360, and Mack G0-J. Supporting data to demonstrate acceptable performance in the following applications: DAF, GB13895(China GL-5), High temperature L37 capable, limited slip, MACK G0J, Meritor 076, ZF TE MI 07A, ZF TE ML 08. PURUS[®] Premium GL-5 Gear Oils are primarily recommended for use in limited slip and conventional differentials of cars, pick up trucks, sport utility vehicles and heavy duty trucks. Always check owner’s manual for proper recommendations.

Suitable for use in applications which cite former or obsolete specifications such as: MIL-L-2105D, MIL-L-2105E, G0-G and G0-H

TYPICAL PROPERTIES*

Viscosity	80W-90	85W-140
Pour Point Deg F.	-15	5
Flash Point, COC, ° F	420	430
Viscosity @ 40° C, cSt	140	345
Viscosity @100° C, cSt	14.6	26.3
Viscosity Index	95	95
Gravity, API	24.5	24.6
Color	2.5	3.0
Rust Test, ASTM D665	PASS	PASS

*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification.
Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

PRODUCT	2/2.5 Gal	35 Lb. Pail	120 Lb. Keg	400 Lb. Drum	Tote	Bulk
80W-90	PHD00534	PHD27173	PHD37173	PHD17173	PHD57173	17173
85W-140		PHD27174	PHD37174	PHD17174	PHD57174	17174