

# PURUS<sup>®</sup>

## CUT THE COST, NOT THE QUALITY.

*"YOU CAN TAKE IT TO THE LAB."*

## PURUS<sup>®</sup> PAPER MACHINE OILS



### DESCRIPTION

PURUS<sup>®</sup> Paper Machine Oils are superior quality, multi-functional lubricants designed for the temperatures, high steam pressures, small sumps, and machine speeds and other adverse conditions found in high-output paper machines employed by full scale paper milling operations. Their combination of advanced additive technology delivers thermally stable machine oils that provide enhanced protection in all facets of performance.

PURUS<sup>®</sup> Paper Machine Oils are specifically made for the lubrication of paper machine equipment in an industrial environment. They are well suited for applications that include use in paper machine circulation systems both wet-end and dryer systems, circulation systems operating in varying and wide-ranging temperatures, lubrication of reduction gears, gear-head motors, vacuum and water pumps, system bearings calendar stacks, as well as hydraulic and other general lubrication applications. Meet the specifications of Voith VN108 Wet/Dry/Press Roll, DIN 51517-2 CL, 51517-3 CLP, 51524-2 HLP, SKF Dry and Valmet Wet/Dry/Zone Rolls.

### TYPICAL PROPERTIES\*

ISO Viscosity Grade	150	220
Specific Gravity	0.875	0.882
Viscosity @100° C, cSt	152	220
Viscosity @40° C, cSt	15.6	19.8
Viscosity Index	105	103
Pour Point, COC, max., °C	-10	-10
Flash Point, min., °C	230	240
Copper Strip Corrosion	1A	1A
Rust, Procedure A/B	Pass/Pass	Pass/Pass
FZG Fail Stage	≥ 12	≥ 12
Emulsion, Time to 3 mL, 82°C	15	15

\*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification.

Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

PRODUCT	55 Gal. Drum	Tote	Bulk
150	PIN16739	PIN66739	16739
220	PIN16740	PIN66740	16740