

PURUS[®]

CUT THE COST, NOT THE QUALITY.

"YOU CAN TAKE IT TO THE LAB."

PURUS[®] ROCK DRILL OILS



DESCRIPTION

PURUS[®] Rock Drill Oils are blended from highly refined base oils and special additives which produce an excellent lubricant for air powered equipment. The naturally high viscosity index provides optimum lubrication for both low start-up temperatures and high operating temperatures. Extreme pressure additives prevent wear and withstand the high loads commonly encountered in rock drills, jack hammers, pavement breakers, stoppers, drifters and down hole drills. PURUS[®] Rock Drill Oils are designed for use in both construction and mining equipment, and other pneumatic equipment applications.

PURUS[®] Rock Drill Oils atomize readily to insure lubricant distribution and rapid "wetting" of all parts of the equipment. By emulsifying with water, they also form a wash off resistant lubricant coating to help prevent rusting of critical components.

PURUS[®] Rock Drill Oils contain tackiness agents that provide lubricant adherence to cylinder walls and other lubricated parts. They are fortified with extreme pressure additives that protect rock drills against wear caused by shock loads.

TYPICAL PROPERTIES*

ISO Viscosity Grade	68	100	150	220	460
API Gravity	29.5	28.1	27.2	27.4	
Viscosity @ 40° C, cSt	68	97.47	142.8	220	460
Viscosity @100° C, cSt	8.7	11.97	15.21	22.04	
Viscosity Index	121	113	108	99	
Pour Point °F	-20	-19	-18	5	

*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification.

Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

PRODUCT	5 Gal. Pail	55 Gal. Drum	Tote	Bulk
68	PIN27191	PIN17191	PIN57191	17191
100	PIN27192	PIN17192	PIN57192	17192
150	PIN27193	PIN17193	PIN57193	17193
220	PIN27194	PIN17194	PIN57194	17194
460	PIN27227	PIN17227	PIN57227	17227